14.19	tit is er ein travet geneta enge faggistlar arbitentelessen er ein einste fer i mis vereitt. De ei s ers et sederest ein sich produktar mattampp travende och net ogste, tennematte
	- Aprodo Posto mandicalnizaira, lum noitonairapo odi piriopo lum modi od - Osto Isamo pud modifica i lagdopopado de wolk antop patopha pais qila - Patomino Isahaji
	h i sa o e e e e e e e e e e e e e e e e e e
	14. Milyalite constitue to the constitue of the fill of the constitue of a fill of the constitue of the cons
787) 787) 788)	12. — 1. Explain how an inductance value config found using a Mark the indesired for a desired for the index of the index
	e populational la digita a logodique de graphar, e, et motopia e e e e e e e e e e e e e e e e e e e
* - 1 ta	BANGER OF THE CONTRACTOR OF TH
;*	A survey call a survey of the influenced) of the confining resigns and region is a finite of the survey of the first of the confining of the survey of the first of the confining of the confinin
	en en en est en marche discognis an marche en en en en fanor Marcheng, en dat elle ste en en

	Reg. No. :						,	: (A)
	Question P							
B.E./B.Tech.	DEGREE EXAMI Th Electronics and (LECTRICAL ENG (Reg	NATION, urd Seme Communic	NOVEM ster ation Er IG AND	IBER/I ngineer INSTR	DECEN ing RUME1	ABER !	2017	
Time: Three Hours				r i seri visy.		mum :	100 M	arks
2. What is back em	f in d.c. motor?	PART A sses are mi	estions: Note and re Anna (10) Inimized On a most of the column of t	orbetti personet brooks resident regident	onland Oracles distant highlad Cignon	1946(1) 1942 =2(1944-14 1946(1)) Mar	rks)
				(5ie):				-
5. Why an induction	n motor never runs	at its sync	hronous	speed?	ogen viete Nami III. Oli gazza	intrologia Inchesia		
6. Why MMF meth method?	od of estimating v	oltage regu	ılation is	s consid	lered a	s optim	nistic	
8. State piezoelectri			1. 1. 1. 1.	Action,	a Teagrain			
9 What is the prine	inla of ware to the little		4 (1)	in the style	The first of the	1100		

9. What is the principle of ramp type digital voltmeter?

10. Name the two different types of storage oscilloscope.

50478

(7)

			PART-B	(S)
11.	a)		Draw and explain the construction and principle of a operation of a DC generator.	(6)
•		ii)	A motor takes an armature current of 110 A at 480 V. The armature circuit resistance is 0.2 Ω the machine has 6-poles and the armature is lap-connected with 864 conductors. The flux per pole is 0.05 Wb. Calculate	
٠,		A.) 	i) the speed and ii) the gross torque developed by the armature.	(7)
	!		OR)	. 20 ¹⁰⁰
	b)		Draw and explain the characteristic of a DC shunt motor and DC series motor. Compare the DC shunt and series motor characteristics and applications.	(6)
i de la composição de l	- Ç - T \$	ii)	A four-pole generator, having wave-wound armature winding has 51 slots, each slot containing 20 conductors. What will be the voltage generated in the machine when driven at 1500 rpm assuming the flux per pole to	(7)
			the 7.0 mWb?	(1)
12.	a)	i)	Draw an ideal single phase transformer and explain the principle of operation, the concept of step up and step down transformer.	(7)
		ii)	Derive the EMF equation of a transformer.	(6)
			(OR)	
	b)	i)	A 25-kVA transformer has 500 turns on the primary and 50 turns on the secondary winding. The primary is connected to 3000-V, 50Hz supply. Find the full load primary and secondary currents, the secondary e.m.f. and the	;
			maximum flux in the core Neglect leakage drops and no-load primary current.	(6)
	•	ii)	A single phase transformer has 500 turns on the primary and 40 turns on the secondary winding. The mean length of the magnetic path in the iron	- "

core is 150 cm and the joints are equivalent to an air-gap of 0.1 mm. When a

potential difference of 3,000 V is applied to the primary, maximum flux

iv) Power factor on no-load. Given that AT/cm for a flux density of 1.2 Wb/m² in iron to be 5, the corresponding iron loss to be 2 watt/kg at 50 Hz

density is 1.2 Wb/m2. Calculate:

i) the cross - sectional area of dia core

iii) the no-load current drawn by the primary

and the density of iron as 7.8 gram/cm³.

ii) no-load secondary voltage

13. a) Draw and explain the construction details and operating principle of an alternator. Also derive the emf equation and draw the vector diagram. (13)b) Draw and explain the construction and principle of operation of three phase slip ring induction motor. How is the construction different in squirrel cage (13)induction motor? 14. a) i) Explain the static and dynamic characteristics of instruments and (7) measurement systems. **(6)** ii) Explain the construction and working of a strain gauge. **(7)** b) i) Explain the construction and working of LVDT. **(6)** ii) Explain the working of a pieze electric transducer. 15. a) i) Explain how an inductance value can be found using a Maxwell's inductance (7)**(6)** ii) Explain the working of a Q meter with neat circuit. **(7)** b) i) Explain the working principle of a digital Oscilloscope. ii) Explain the construction and working of Digital voltmeter with neat block (6) diagram. $(1\times15=15 \text{ Marks})$ PART-C 16. a) Derive the torque equation and also the condition for maximum torque under starting and running condition. (OR) b) Derive the equation for unknown resistance using wheatstone bridge.