Reg. No. :

Question Paper Code : 27122

B.E./B.Tech. DEGREE EXAMINATION, NOVEMBER/DECEMBER 2015.

Fifth Semester

Civil Engineering

CE 6502 — FOUNDATION ENGINEERING

(Regulation 2013)

Time : Three hours

Maximum : 100 marks

Answer ALL questions.

PART A — $(10 \times 2 = 20 \text{ marks})$

- 1. What is mean dilatancy?
- 2. Write the uses of bore hole report.
- 3. What is the allowable maximum settlement of commercial, Industrial and ware house building?
- 4. What is the ultimate hearing capacity of a circular footing of 1.5 m diameter resting on the surface of a saturated clay of unconfined compressive strength of 100 kN/m^2 Take N_c = 5.7, N_g = 1, N_r = 0, $\sigma = r$ D = 0.
- 5. List out the types of footing.
- 6. Write the components of total settlement?
- 7. What are the methods available to determine Load caring capacity of pile?
- 8. For a pile designed for an allowable load of 400 kN driven by a Steam hammer (Single acting) with a energy of 221 t-cm, what is the approximate terminal set of pile?
- 9. Define surcharge angle.
- 10. What force is acting on retaining wall?

PART B — $(5 \times 16 = 80 \text{ marks})$

Explain in detail about the geophysical method of site exploration with 11. (a) · neat sketch.

Or

- Write short notes on : (b)
 - Selection of Foundation based on soil condition (i) (8)
 - (ii) Disturbed and Undisturbed soil sample
 - (iii) Uses of soil Exploration.
- A strip footing 2 m wide carries a load intensity of 560 kN/m² at a depth 12. (a) of 1.2 m in sand. The saturated unit weight of sand is 18 kN/m³ and unit weight have a water table is 16.8 kN/m³.

The shear strength parameters are C = 0 and $\phi = 35^{\circ}$ determine the factor safety with respect to shear failure for the following cares of location of water table.

- (i) Water table is 3 m below ground level
- Water table is at G.L itself level (ii)
- (iii) Water table is 4 m below ground level
- (iv) Water table is 0.5 m below level.

Write brief notes on :

(b)

Or

- Explain in detail about IS code method for computing the bearing (b) capacity of soil with various types of failure and shape factor.
- (a) Discuss in detail about the design producer for Rectangular combine 13. footing and Trapezoidal combine footing with suitable sketch.

Or

| (i) | Mat Foundation | (6) |
|-------|--|-----|
| (ii) | Floating Foundation | (6) |
| (iii) | Seismic force consideration in footing design. | (4) |

Explain in details about the various types of pile foundation with neat 14. (a) sketch and write their functions.

Or

| (b) | Write short notes on : | | | |
|-----|------------------------|-----------------------------------|-----|--|
| | (i) | Negative skin friction | (5) | |
| | (ii) | Under reared piles | (4) | |
| | (iii) | Piles Cap | (2) | |
| | (iv) | Settlement of pile group in clay. | (5) | |

(4)

(4)

(16)

15. (a) Explain in details about the CUL MANN's graphical method for finding active pressure with a neat sketch.

Or

- (b) Discuss in detail about the Rankines theory for the following cases of cohesions soil and cohesive soil.
 - (i) Submerged back fill
 - (ii) Back fill with sloping surface.

(8)

(8)